

City Research Online

City, University of London Institutional Repository

Citation: Jimenez-Ruiz, E. (2021). LogMap Family Participation in the OAEI 2021. CEUR Workshop Proceedings, 3063, pp. 175-177. ISSN 1613-0073

This is the published version of the paper.

This version of the publication may differ from the final published version.

Permanent repository link: https://openaccess.city.ac.uk/id/eprint/27581/

Link to published version:

Copyright: City Research Online aims to make research outputs of City, University of London available to a wider audience. Copyright and Moral Rights remain with the author(s) and/or copyright holders. URLs from City Research Online may be freely distributed and linked to.

Reuse: Copies of full items can be used for personal research or study, educational, or not-for-profit purposes without prior permission or charge. Provided that the authors, title and full bibliographic details are credited, a hyperlink and/or URL is given for the original metadata page and the content is not changed in any way.

City Research Online:

http://openaccess.city.ac.uk/

publications@city.ac.uk

LogMap Family Participation in the OAEI 2021 *

Ernesto Jiménez-Ruiz^{1,2}

Department of Computer Science, City, University of London, UK
Department of Informatics, University of Oslo, Oslo, Norway

Abstract. We present the participation of LogMap and its variants in the OAEI 2021 campaign. The LogMap project started in January 2011 with the objective of developing a scalable and logic-based ontology matching system. This is the eleventh participation in the OAEI and the experience has so far been very positive. LogMap is one of the few systems that participates in (almost) all OAEI tracks.

1 Presentation of the system

LogMap [9, 11] is a highly scalable ontology matching system that implements the consistency and locality principles [10]. LogMap is one of the few ontology matching system that (i) can efficiently match semantically rich ontologies containing tens (and even hundreds) of thousands of classes, (ii) incorporates sophisticated reasoning and repair techniques to minimise the number of logical inconsistencies, and (iii) provides support for user intervention during the matching process. LogMap ISWC 2011 paper [9] has recently been awarded the SWSA Ten-Year Award.³

1.1 LogMap variants in the 2021 campaign

As in previous campaigns, in the OAEI 2021 we have participated with two additional variants:

LogMapLt is a "lightweight" variant of LogMap, which essentially only applies (efficient) string matching techniques.

LogMapBio includes an extension to use BioPortal [6, 7] as a (dynamic) provider of mediating ontologies instead of relying on a few preselected ontologies [3].

In previous years we also participated with LogMapC⁴.

^{*} Copyright © 2021 for this paper by its authors. Use permitted under Creative Commons License Attribution 4.0 International (CC BY 4.0).

http://swsa.semanticweb.org/content/swsa-ten-year-award

⁴ LogMapC (https://github.com/asolimando/logmap-conservativity/) is a variant of LogMap which, in addition to the consistency and locality principles, also implements the conservativity principle (see details in [13]).

1.2 Link to the system and parameters file

LogMap is open-source and released under the Apache-2.0 License.⁵ LogMap components and source code are available from the LogMap's GitHub page: https://github.com/ernestojimenezruiz/logmap-matcher/.

LogMap distributions can be easily customized through a configuration file containing the matching parameters.

LogMap, including support for interactive ontology matching, can also be used directly through an AJAX-based Web interface: http://krrwebtools.cs.ox.ac.uk/. This interface has been very well received by the community since it was deployed in 2012. More than 5,500 requests coming from a broad range of users have been processed so far.

1.3 LogMap as a mapping repair system

Only a very few systems participating in the OAEI competition implement repair techniques. As a result, existing matching systems (even those that typically achieve very high precision scores) compute mappings that lead in many cases to a large number of unsatisfiable classes.

We believe that these systems could significantly improve their output if they were to implement repair techniques similar to those available in LogMap. Therefore, with the goal of providing a useful service to the community, we have made LogMap's ontology repair module (LogMap-Repair) available as a self-contained software component that can be seamlessly integrated in most existing ontology matching systems [12, 5].

1.4 LogMap as a matching task division system

LogMap also includes a novel module to divide the ontology alignment task into (independent) manageable subtasks [8]. This component relies on LogMap's lexical index, a neural embedding model [14] and locality-based modules [4]. This module can be integrated within existing ontology alignment systems as a external module to support them complete large-scale matching tasks.

2 General comments and conclusions

Please refer to http://oaei.ontologymatching.org/2021/results/ for the results of the LogMap family in the OAEI 2021 campaign.

2.1 Comments on the results

As in previous campaigns, LogMap has been one of the top systems and one of the few systems that participates in (almost) all tracks. Furthermore, it has also been one of the few systems implementing repair techniques and providing (almost) coherent mappings in all tracks.

⁵ http://www.apache.org/licenses/

LogMap's main weakness is that the computation of candidate mappings is based on the similarities between the vocabularies of the input ontologies; hence, in the cases where the ontologies are lexically disparate or do not provide enough lexical information LogMap is at a disadvantage.

2.2 Future work

LogMap is being extended in combination with machine learning techniques and ontology embeddings based on language models (e.g., OWL2Vec* [1]) Preliminary results of LogMap-ML have been recently published [2]. We aim at targeting the OAEI 2022 with a fully-fledged system.

Acknowledgements. I would also like to thank Bernardo Cuenca-Grau, Ian Horrocks, Alessandro Solimando, Jiaoyan Chen, Valerie Cross, Anton Morant, Yujiao Zhou, Weiguo Xia, Xi Chen, Yuan Gong and Shuo Zhang, who have contributed to the LogMap project in the past.

References

- Chen, J., Hu, P., Jiménez-Ruiz, E., Holter, O.M., Antonyrajah, D., Horrocks, I.: OWL2Vec*: embedding of OWL ontologies. Mach. Learn. 110(7), 1813–1845 (2021)
- Chen, J., Jiménez-Ruiz, E., Horrocks, I., Antonyrajah, D., Hadian, A., Lee, J.: Augmenting ontology alignment by semantic embedding and distant supervision. In: 18th Extended Sem. Web Conf. (ESWC). pp. 392–408 (2021)
- 3. Chen, X., Xia, W., Jiménez-Ruiz, E., Cross, V.: Extending an ontology alignment system with bioportal: a preliminary analysis. In: Poster at Int'l Sem. Web Conf. (ISWC) (2014)
- 4. Cuenca Grau, B., Horrocks, I., Kazakov, Y., Sattler, U.: Modular reuse of ontologies: Theory and practice. J. Artif. Intell. Res. 31, 273–318 (2008)
- Faria, D., Jiménez-Ruiz, E., Pesquita, C., Santos, E., Couto, F.M.: Towards annotating potential incoherences in bioportal mappings. In: 13th Int'l Sem. Web Conf. (ISWC) (2014)
- 6. Fridman Noy, N., Shah, N.H., Whetzel, P.L., Dai, B., et al.: BioPortal: ontologies and integrated data resources at the click of a mouse. Nucleic Acids Research 37, 170–173 (2009)
- 7. Ghazvinian, A., Noy, N.F., Jonquet, C., Shah, N.H., Musen, M.A.: What four million mappings can tell you about two hundred ontologies. In: Int'l Sem. Web Conf. (ISWC) (2009)
- Jiménez-Ruiz, E., Agibetov, A., Chen, J., Samwald, M., Cross, V.: Dividing the Ontology Alignment Task with Semantic Embeddings and Logic-Based Modules. In: 24th European Conference on Artificial Intelligence (ECAI). pp. 784–791 (2020)
- 9. Jiménez-Ruiz, E., Cuenca Grau, B.: LogMap: Logic-based and Scalable Ontology Matching. In: Int'l Sem. Web Conf. (ISWC). pp. 273–288 (2011)
- Jiménez-Ruiz, E., Cuenca Grau, B., Horrocks, İ., Berlanga, R.: Logic-based assessment of the compatibility of UMLS ontology sources. J. Biomed. Sem. 2 (2011)
- 11. Jiménez-Ruiz, E., Cuenca Grau, B., Zhou, Y., Horrocks, I.: Large-scale interactive ontology matching: Algorithms and implementation. In: Europ. Conf. on Artif. Intell. (ECAI) (2012)
- 12. Jiménez-Ruiz, E., Meilicke, C., Cuenca Grau, B., Horrocks, I.: Evaluating mapping repair systems with large biomedical ontologies. In: 26th Description Logics Workshop (2013)
- Solimando, A., Jiménez-Ruiz, E., Guerrini, G.: Minimizing conservativity violations in ontology alignments: Algorithms and evaluation. Knowledge and Information Systems (2016)
- 14. Wu, L., Fisch, A., Chopra, S., Adams, K., Bordes, A., Weston, J.: Starspace: Embed all the things! arXiv preprint arXiv:1709.03856 (2017)